



Ockwells FleeceShield Standard

Product type

FleeceShield Standard Multifunctional nonwoven with adhesive coating with OPTICOAT™

Characteristic Properties

Material Nonwoven synthetic fibres
Top side with PE sheet acting as barrier against liquids
Rear side with slip resistant coating OPTICOAT™

Colour White

Technical Properties

Thickness 2mm

Water vapour permeability

Water in permeability

Water absorption ability

Advantages

Protects floors, carpets, stairs, tiles, etc. (E.g. from mechanical damage or stains from spilled liquids).
Helps to prevent accidents (Rear side with active protection against slipping).
Can be used several times, quickly laid out (Cost saving).
Environment-friendly (Free of harmful substances, thermally disposable).

Important

FleeceShield Standard is not suitable for newly laid floors, porous stone floors and clay tiles.

Laying

With overlap of 10 cm

Function / Application

Safe and highly effective protection for floors and surfaces of all kinds, including; carpets, tiles, furniture, etc.

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk