



Glass Protection Film

Description

Ockwells Glass Protection Film is a 35 micron polythene surface protection film coated with a low tack solvent acrylic adhesive system. Good resistance to moisture, sunlight and variable climatic conditions. This Glass Film is UV Stable for up to 6 months. Product Code = 10066206.

Applications

Ockwells glass protection film should only be used on plain float glass.

Specifications

No.	Measured Aspect	Unit	Specification Requirement
1	Backing Film		PE Film
2	Adhesive		Acrylic
3	Colour		Transparent Clear
5	Thickness	mm	0.035 ± 0.005
6	Width	mm	500 ± 1
7	Internal Diameter	mm	76 ± 0.5
8	Adhesive Strength	g/50mm	380 ± 10%
10	Elongation at Break	%	≥ 300
11	Temperature Resistance		60°C, 160 hours - no residue glue remains on the glass surface after removal
12	Length	m	100 ± 1

Ockwells glass protection film is a 35 micron film that can be left on glass externally for up to 4 weeks and internally for up to 6 months and should then be replaced.

The company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Please check that you have the latest issue of the information sheet.

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,
Berkshire RG19 4ZA

T: 01635 876336
sales@ockwells.com

WARRINGTON

Unit 12, Cameron Court,
Winwick Quay,
Warrington WA2 8RE

T: 01925 820003
sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Mackellan Street,
Kinning Parkway Estate,
Glasgow G41 1RR

T: 0141 427 3366
sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View Business Centre
Fairview Industrial Park
Rainham RM13 8BT

T: 020 7473 8770
sales.rainham@ockwells.com