



Ockwells Hazard Warning PVC Tape

Description

Manufactured from a plasticised polyvinyl chloride film and coated with an aggressive pressure sensitive rubber-based adhesive.

Applications

- Hazard Tape should be used to highlight hazards in and around construction sites
- Used on scaffolding poles and as a warning tape around trenches etc

Properties	Unit	Value
Total thickness	µm	150 ± 10
Adhesive	-	Rubber
Elongation	%	85
Initial Tack (Ball Test)	Ball no	≥ 10
180° Peel Adhesion	N/IN	≥ 2.5
Tensile Strength	N/IN	≥ 35
Service temperature	°C	0 ~ +80
Storage temperature	°C	Normal room temp.
Shelf life	Month	24

Unless otherwise indicated the figures above are average values and should not be treated at face value for specification purposes.

Application surface should be clean, dry and free of grease, oil, moisture, dirt, and other conditions.

Due to the different properties and characteristics of material surfaces, the purchaser and or user should test the suitability of the tape in an unexposed area to satisfy themselves that the tape is suitable for their requirements.

If unsure of the products suitability - DO NOT USE!

NEWBURY

Unit 6, Transigo,
Gables Way, Thatcham,

Berkshire RG19 4ZA

T: 01635 876336

sales@ockwells.com

WARRINGTON

Unit 12, Cameron Court,
Winwick Quay,

Warrington WA2 8RE

T: 01925 820003

sales.warrington@ockwells.com

GLASGOW

Unit 2, 45 Mackellan Street,
Kinning Parkway Estate,

Glasgow G41 1RR

T: 0141 427 3366

sales.glasgow@ockwells.com

EAST LONDON

Unit E1, Thames View Business Centre
Fairview Industrial Park

Rainham RM13 8BT

T: 020 7473 8770

sales.rainham@ockwells.com