

FR Debris Netting – CF5764

Product Description:

Certificated Flame-Retardant Debris Netting certified to TS62 Standard.
Each sheet features lengthwise reinforced black buttonholes spaced approximately 15cm apart for secure fastening.

Product Features:

Fire Resistant – Certificated TS62 – CF5764
Provides screening whilst letting air through (reducing pressure on scaffold)
UV additive to help protect net from degradation.
Range of colours available.
Installed with cable / netting ties.

Product Specifications:

- 2m x 50m – 60GSM Coverage 100m²
- 3m x 50m – 60GSM Coverage 150m²

Performance Data:

Materials:	High Density Polyethylene Monofilament knitted yarn.
Weave:	PE Monofilament
Tensile Strength:	Warp 400N/50mm, Weft 245N/50mm
Colours:	White, Blue, Black, Green, Grey, Yellow.
Air Permeability:	40%
Shade Factor:	30%

Version Date: 04/08/25

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336

sales@ockwells.com

WARRINGTON

01925 820003

sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366

sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770

sales.eastlondon@ockwells.co.uk