


Scaffold Sheeting Standard

Reinforced polyolefin sheeting system for temporary containment and weather protection applications. Powerclad reinforcement bands incorporate eyelets every 10cm to provide a versatile system for all tube & fitting and modular scaffold systems and the ability to vary the support density according to anticipated wind forces.

PRODUCT	Flame retardant 	Colour	Weight EN 695 gsm	Tensile strength BS 7955 N/50mm	Eyelet strength BS 7955 Newtons	Conforms to	Temperature range °C	Aerodynamic coefficient EN ISO 9237 Cf	Sizes metres	Roll weight kg	Pallet quantity
NON-FLAME RETARDANT SHEETING											
Powerclad Standard XL	NA	Clear	180	MD >630 XD >630	>500	BS 7955	-40 to +70	1.0	4.0 x 45	32.9	23
Powerclad Standard	NA	Clear	170	MD 500 XD 500	>500	NA	-40 to +70	1.0	2.0 x 45 2.2 x 40 3.0 x 45 2.7 x 20	15.8 15.4 23.5 9.0	39 39 23 50
Powerclad Lite	NA	Clear	150						2.0 x 45		

Fastening ties: Elasticated Toggle Ties BS 7955 Pass break strength 500 N (28cm reach)

Flexo printing: Maximum print area 1070 x 730mm; repeats at 1270mm; up to 2 colours; subject to minimum quantities

Ockwells are a division of SIG Trading Ltd. SIG Trading Ltd terms and conditions of sale apply to all transactions. A copy can be provided on request and will be incorporated into the contract of sale.

Version Date: June 2025

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336

sales@ockwells.com

WARRINGTON

01925 820003

sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366

sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770

sales.eastlondon@ockwells.co.uk