



Ockwells FleeceShield Flame Retardant

Product type

FleeceShield Flame Retardant Multifunctional, vapour-transmitting protective nonwoven with adhesive coating with OPTICOAT™

Characteristic Properties

Material Nonwoven flame retardant synthetic fibres
Top side with PE sheet acting as barrier against liquids
Rear side with slip resistant coating OPTICOAT™

Colour White/Green

Technical Properties

Thickness 1.5mm

Certification Wheelmark (no. 0098/16) according to IMO res. MSC.307(88)
- 2010 FTP Code, annex1, part 5

Fire Classification Bfl s1 according EN 13501-1

Advantages

Wheelmark certification according to IMO standards.
Protects floors, carpets, stairs, tiles, etc. (E.g. from mechanical damage or stains from spilled liquids).
Helps to prevent accidents (Rear side with active protection against slipping).
Can be used several times, quickly laid out (Cost saving).
Environment-friendly (Free of harmful substances, thermally disposable).
Vapour-transmitting.

Important

FleeceShield Flame Retardant is not suitable for newly laid floors, porous stone floors and clay tiles.

Laying

With overlap of 10 cm

Function / Application

Safe and highly effective protection for floors and surfaces of all kinds, including; carpets, tiles, furniture, etc.

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk