



Ockwells ProShield TS63 Flame Retardant

Description

ProShield is manufactured from a durable, waterproof, and flame-retardant woven polyethylene, for use in a wide range of applications.

Applications

ProShield can be used to protect vinyl and carpet flooring in construction and renovation projects.

Technical Details	
Total thickness:	100um
Total weight:	80gsm
Colours:	White
Size:	1.5m x 10m folded packs 1.5m x 67.5m rolls
Certification:	Warrington Certification TS63 No. CF 5484
Custom printing:	Please contact one of our sales offices for availability

Ockwells ProShield or other similar non adhesive sheeting products are designed to protect all kinds of floor surfaces, we recommend that the protection is fixed firmly using an appropriate tape or fixing.

We also recommended that any spillages are dealt with immediately to avoid any potential risk of slip or falls.

The company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Please check that you have the latest issue of the information sheet.

Issue Date: October 2023

These properties are the Manufacturers' typical values based on the average of several tests. As the installation and handling of this product is beyond our control the user must ensure that the product is suitable for the application. Ockwells cannot accept responsibility for any loss or damage that may occur either directly or indirectly using this product. Ockwells also holds the right to change specification data without prior notice

NEWBURY

01635 876336
sales@ockwells.co.uk

WARRINGTON

01925 820003
sales.warrington@ockwells.co.uk

GLASGOW

0141 427 3366
sales.glasgow@ockwells.co.uk

EAST LONDON

020 7473 8770
sales.eastlondon@ockwells.co.uk